



HIGH PRESSURE COUPLINGS AND FITTINGS

W.P. 4100 BAR



WWW.PRO-JETTING.COM

High Pressure Couplings and Fittings

Couplings, adapters, T-pieces, Y-pieces and Collar and Glands | W.P. 4100 bar (60,000 psi)

The cheapest ultra high pressure couplings / adapters / T- pieces / Y- pieces / Gland and Collar. Suitable to a maximum of 4100 bar (60.000 psi).



Specifications

Max. Working Pressure: 4100 bar (60,000 psi)

Connections: 1/4" HP, 3/8" HP, 9/16" HP, M16, M20, M30

Types: Coupling, Adapter, T- Piece, Y- Piece, Gland and Collar

Features

- Well priced
- Volume discount
- High quality

	Item	Type	W.P.	Connections
	Z-AF-U09	Coupling	4100 bar (60,000 psi)	9/16" HP (1 1/8" UNF)
	Z-AF-U06	Coupling	4100 bar (60,000 psi)	3/8" HP (3/4" UNF)
	Z-AF-M16	Coupling	4100 bar (60,000 psi)	M6 (M16x1,5) HP
	Z-AF-M20	Coupling	4100 bar (60,000 psi)	M10 (M20x1,5) HP
	Z-AF-M30	Coupling	4100 bar (60,000 psi)	M14 (M30x2) HP
	Z-AF-U09-U06	Adapter	4100 bar (60,000 psi)	9/16" HP - 3/8" HP (1 1/8" UNF - 3/4" UNF)
	Z-AF-U06-U04	Adapter	4100 bar (60,000 psi)	3/8" HP - 1/4" HP (3/4" UNF - 9/16" UNF)
	Z-TF-U09	T- Piece	4100 bar (60,000 psi)	9/16" HP (1 1/8" UNF)
	Z-TF-U06	T- Piece	4100 bar (60,000 psi)	3/8" HP (3/4" UNF)
	Z-TF-M16	T- Piece	4100 bar (60,000 psi)	M6 (M16x1,5) HP
	Z-TF-M20	T- Piece	4100 bar (60,000 psi)	M10 (M20x1,5) HP
	Z-TF-M30	T- Piece	4100 bar (60,000 psi)	M14 (M30x2) HP
	Z-YF-U09	Y- Piece	4100 bar (60,000 psi)	9/16" HP (1 1/8" UNF)
	Z-YF-U06	Y- Piece	4100 bar (60,000 psi)	3/8" HP (3/4" UNF)
	Z-YF-M16	Y- Piece	4100 bar (60,000 psi)	M6 (M16x1,5) HP
	Z-YF-M20	Y- Piece	4100 bar (60,000 psi)	M10 (M20x1,5) HP
	Z-YF-M30	Y- Piece	4100 bar (60,000 psi)	M14 (M30x2) HP
	Z-GL-U09	Gland	4100 bar (60,000 psi)	1 1/8" UNF HP
	Z-GL-U06	Gland	4100 bar (60,000 psi)	3/4" UNF HP
	Z-GL-U04	Gland	4100 bar (60,000 psi)	9/16" UNF HP
	Z-GL-M16	Gland	4100 bar (60,000 psi)	M16 HP
	Z-GL-M20	Gland	4100 bar (60,000 psi)	M20 HP
	Z-GL-M30	Gland	4100 bar (60,000 psi)	M30 HP
	Z-CO-UL09	Collar	4100 bar (60,000 psi)	9/16" HP
	Z-CO-UL06	Collar	4100 bar (60,000 psi)	3/8" HP
	Z-CO-UL04	Collar	4100 bar (60,000 psi)	1/4" HP
	Z-CO-ML6	Collar	4100 bar (60,000 psi)	M6 LH HP
	Z-CO-ML10	Collar	4100 bar (60,000 psi)	M10 LH HP
	Z-CO-ML14	Collar	4100 bar (60,000 psi)	M14 LH HP